

IKA

designed for scientists



RT 5

/// Data Sheet

5-position digital magnetic hotplate stirrer, designed for synchronous heating and stirring. The magnetic coil technology provides noiseless and consistent stirring on all positions. The surface temperature is infinitely adjustable up to 120 °C, producing a maximum medium temperature of 70 °C (depending on the used vessel). Speed remains constant, even when load changes.

- Homogeneous temperature distribution across the heating plate
- Adjustable reverse operation
- Eco-mode for a low self-warming of the surface
- Wear free magnetic coil
- Error code displa
- Easy operation with touch keypa
- Suitable for continuous operatio
- Speed range: 0 - 1000 rp



designed for scientists

Technical Data

Number of stirring positions	5
Stirring position distance [mm]	90
Speed deviation of individual stirring positions [%]	0
Stirring quantity max. per stirring position (H2O) [l]	0.4
Speed control	10 RPM Steps
Speed range [rpm]	0 - 1000
Stirring bar length [mm]	25 - 30
Heat output [W]	175
Heating temperature range [°C]	Room temp. - 120
Heat control	LED
Heating rate heating plate [K/min]	3
Adjustable safety circuit [°C]	50 - 150
Set-up plate material	Aluminium alloy
Set-up plate dimensions [mm]	110 x 495
Dimensions (W x H x D) [mm]	120 x 60 x 610
Weight [kg]	4
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 40
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	200

www.imlab.eu

info@imlab.be - Tél. : +32 (0)16 73 55 72

imLab

www.imlab.eu

info@imlab.fr - Tél. : +33 (0)3 20 55 19 11

Imlab sprl - Oude Vijvers, 1
3370 Boutersem - Belgique

Imlab sarl - Centre d'Affaires de l'Horlogerie
48 rue des Canoniers - 59000 Lille - France